

Transfer grilles AP





Aluminum transfer grilles AP are intended for redistribution of air in rooms. Grilles consist of two rectangular frames: external and internal. V-shaped horizontal louvers that prevent the view through the grille are fixed rigidly in the internal frame. The external frame is mounted in the door or the wall aperture and fixed with self-tapping screws. The internal frame is mounted at the opposite side of the door or the wall. The sizes of frames enable to mount grilles on doors or thin partitions $25 \div 50 \text{ mm}$ thick.

Transfer grilles are made of aluminum and are powder coated beige color (RAL 9015).

Minimal size 100×100 mm, maximal 1000×200 mm, spacing – 50 mm. Any other size may be available upon Customer's request.

Technical characteristics of grilles of the sizes available at the works' warehouse are presented in the table below.





Data for selection of transfer grilles AP

	F ₀ ,	F _{eff} , m ²	V _{eff} , m/s							
A × B, mm			0,2	0,4	0,6	0,8	1,0	1,5	2,0	2,5
			ΔP_{t} , Pa							
			0, I	0,3	0,7	1,3	2,0	4,0	8,0	12,0
			L ₀ , m³/h							
300 × 150	0,04	0,02	15	30	45	60	80	110	150	190
300 × 200	0,05	0,03	21	42	63	80	100	160	210	260
300 × 250	0,07	0,04	26	52	78	100	130	190	260	320
350 × 150	0,05	0,03	18	36	54	70	90	140	180	230
350 × 200	0,06	0,03	24	49	73	100	120	180	240	310
400 × 150	0,05	0,03	21	42	63	80	100	160	210	260
400 × 200	0,07	0,04	29	58	86	120	140	220	290	360
500 × 150	0,07	0,04	27	53	80	110	130	200	270	330
500 × 200	0,09	0,05	36	72	110	140	180	270	360	450
500 × 250	0,12	0,06	46	92	140	180	230	350	460	580
600 × 200	0,11	0,06	44	88	130	180	220	330	440	550
600 × 250	0,14	0,08	56	110	170	220	280	420	560	700